



**32586 477th Ave.  
Elk Point, SD 57025  
(800) 447-3924  
fx: (605) 356-2144  
www.steeleagle.com  
info@steeleagle.com**

## **24" Surface Spinner**



**ASE-0017U**

### Standard Features:

All Metal Chassis and Aluminum Deck  
24" Cleaning Path  
Trigger Gun built into handle for easy use.  
3/8" Quick Coupler nipple for easy hose hookup.  
Mosmatic Swivel Union  
High RPM Swivel features reinforced self lubricated stainless steel ball bearings and dual spring based carbide seals for long lasting operation under tough conditions.

Throughput Medium: pH 3-12

Min. Pressure: 1500 PSI

Max Pressure: 4000 PSI

Max Temperature: 250 F

RPM: Maximum 2000 RPM

Rebuild kits available for easy maintenance.

1/8" thick Spun Aluminum Deck; Durable, yet light weight

Durable Baked-on Powder-Coat Paint handle.

Large 10" Pneumatic rear tires for easy rolling.

Large 3" Front caster for maneuverability.

Stainless Steel Spray arm assembly.

2 nozzle Spray arm assembly standard.

#15025 1/4" MEG nozzles standard.

Other nozzle sizes available upon request.

Minimum recommended flow rate 3 gallons per minute.

Maximum flow rate of 10 gallons per minute.

6 Month Warranty

Made in USA